

# Wax Ribbon

# C11

## Description

Provides superior image while printing at high speeds. Ideal for small to wipe URB printing. Exceptional print images, with deep dark barcodes and text. Good durability. Easy to use, drop into any printer, no adjustments needed. Anti-static ink and back coat formulation makes this ribbon the choice for RFID printing. Perfect for any general purpose printing.

## Product Details

- Outstanding print performance on coated stocks
- Prints at lower energy settings
- Offers higher durability than most waxes
- Specially formulated backcoat protects the printhead
- Economical and excellence for general purpose labeling with excellent print performance.
- REACH and ROHS approved

## Recommended Substrates

Coated/uncoated paper, gloss paper, synthetic paper, polypropylene.



## Applications



## Settings



## Durability / Printed Image



## Ribbon Property

Description	Specifications
Ink Material	Wax
Total Thickness (µm)	8.5
Base Film Thickness (µm)	4.5
Ink Thickness (µm)	3.9
Ribbon Transmission Density	2.7 MacBeth Scale
Print Density	1.9
Ink Melting Point	65°C/149°F

## Compliances

REACH – SVHC Free  
 RoHS/WEEE TSCA  
 CONEG  
 California Proposition 65  
 TSCA  
 Additional Regulatory Requirements Upon Request